







## Application Note 0051

# How to Setup the Old Bluetooth Scanner

This How to Guide is used for pairing the old cream / white Seaward Bluetooth scanner (pictured) to your Apollo **Series**. Please check all aspects of this before contacting the technical support helpline.











## Pairing with the Apollo Series Instruments

- 1) Please register your Apollo to receive an additional 12 months warranty plus full access to Product Support. You can do this at [www.seaward.co.uk/warranty24](http://www.seaward.co.uk/warranty24) or by completing the form in the "Care and Support" card and returning by post.
- 2) Please ensure your Apollo has the latest firmware installed, to do this please see the following link: [www.seaward.co.uk/apollo-series-firmware](http://www.seaward.co.uk/apollo-series-firmware)
- 3) Initial Configuration of the scanner:
  - (a) Make sure the batteries are fitted and working correctly.
  - (b) Press the trigger and scan the set up codes 1 to 8 overleaf in the correct order. (The scanner will beep after reading each barcode)
  - (c) Press the trigger to scan code 9, this will cause the light to start flashing blue
- 4) From the Apollo "Home Screen"  press the Menu button "F4". 
- 5) In the menu select Bluetooth by pressing key number "3". 
- 6) The 'Bluetooth active' symbol will appear next to the battery symbol. 
- 7) On the Apollo press the Bluetooth search button "F2"  (hint: it helps if the scanner is the only Bluetooth device turned on at this time, if it is not flashing blue repeat step 3)
- 8) Select the "Bar Code" field on the Apollo (using the arrow keys) and from the drop down select, the device named "OPL2724\_ . . ."
- 9) Press "F4"  to save the new Bluetooth configuration
- 10) You can now use the scanner to enter information such as asset IDs.

## Application Note 0051

## Initial Configuration of the Scan Steps 1 to 9:

1.	 Z Z	SET (places scanner into setup mode)
2.	 E N A U	Enable Auto Connect
3.	 P C O 5	Enable Trigger Connect (Press and hold trigger for 5 seconds for a manual connection)
4.	 P D O 8	Enable Trigger Disconnect (Press and hold trigger for 8 seconds for a manual disconnection)
5.	 A D O 1	Power Save Mode (Scanner will disconnect if idle for 10 minutes)
6.	 C A O 5	Auto Reconnect (Scanner will attempt to reconnect for 5 minutes)
7.	 B B D	Trigger to Make connectable
8.	 Z Z	END

Application



+ - D S C O - +

Scan to make device discoverable